




# PureCal™ 3m

Calcium Carbonate

### Description:

PureCal is produced from an underground high calcium limestone deposit. "Calcite" and "ground limestone" are synonymous with ground natural "calcium carbonate".

- Sized by air separation process to consistently meet exact specifications.
- Ideal for and mineral suspension applications, water dispersible products.
- Applications in paints, plastics, and rubber production.



Mean Particle Size: 3.2 Microns

### CHEMICAL SPECIFICATIONS

	TYPICAL
Calcium (Ca)	39.50%
Calcium Carbonate (CaCO <sub>3</sub> )	98.30%

### TYPICAL PHYSICAL CHARACTERISTICS

Bulk Density (loose)	62 lbs/ft <sup>3</sup>
Bulk Density (compacted)	78 lbs/ft <sup>3</sup>
Moisture	< 0.05%
Appearance	off white
pH (ASTM - D1208)	9.3

### IMPURITIES, TYPICAL

Magnesium	(Mg)	0.20%
Silica	(SiO <sub>2</sub> )	0.30%
Iron	(Fe)	0.0456%
Aluminum	(Al)	0.0010%
Arsenic	(As)	< 0.5 ppm
Cadmium	(Cd)	< 0.8 ppm
Lead	(Pb)	< 3.2 ppm
Mercury	(Hg)	< 0.1 ppm

Cerne Calcium Company  
2123 200<sup>th</sup> Street  
Fort Dodge, IA 50501

Ordering Information:  
515.223.8844  
orders@cernecalcium.com



Cerne Calcium Company (CCC) does not intend or represent that this information or the products to which it relates be used in any manner which would or could infringe patent rights of others. Although we believe the sources of this information to be reliable, CCC disclaims any responsibility or liability for results of using this information since conditions of use are beyond our control.